

Product Data

Driwall™ Membrane Primer WB

A Water-based, Black Asphalt Emulsion Primer

Description

Driwall™ Membrane Primer WB is a fast drying, water-based, black asphalt emulsion primer. Designed to require a minimum amount of mixing before applications, Driwall Membrane Primer WB meets DOT standards for SS1h and ASTM D977. Formulated to have outstanding performance with all Keene Driwall Membrane products, Driwall Membrane Primer WB will also work with most asphalt based waterproofing membranes. Driwall Membrane WB primer is suitable for use over wood (OSB), cement, asphalt, gypsum, cinder block, and most porous substrates providing a superior binding surface.

Packaging

5 gallon pail

Features and Benefits

- Fast drying
- Easy clean up
- Requires minimal mixing
- Usable over a wide range of substrates

Application

Suitable for any Driwall Membrane application
Usable over a wide variety of substrates

Ensure all surfaces to be primed are dry and free of any oil or grease. All surfaces must be clean and free of dust, dirt and any foreign material. Thoroughly mix product **BEFORE** application. For best results use when substrate temperature is above 50°F. *Note: low temperatures and/or high humidity may extend drying time.* Apply using a medium nap roller or a soft bristled brush. Allow to dry for a minimum of 30min (until coating is slightly tacky to the touch). Before applying Keene Driwall Membrane. If primer is allowed to dry more than 24hr, recoat before applying waterproofing membrane. Cleanup using soap and water.

General Guidelines

- KEEP FROM FREEZING
- MIX PRIOR TO APPLICATION
- Close container after each use
- Use appropriate protective clothing and eye protection
- Avoid prolonged exposure to skin, use in adequately ventilated area
- Keep out of reach of children
- DO NOT INGEST

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The foregoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.