

Product Data

Driwall™ CDR Vent Complete Drained Roof

Description

Driwall™ CDR Vent is a 0.30-inch, randomly oriented, geometric patterned drainage and ventilation mat.

The product is designed to eliminate moisture and moisture vapor in cedar roofing, siding applications, and metal roofing applications.

Driwall™ CDR Vent is produced from an extruded polymer matrix of tangled monofilaments, which are heat-welded at the junctions to form a structure that spaces siding and roofing away from the inner sheathing.

The product is useful in cedar and metal roofing and siding applications in which a clean airspace is desired for ventilation and drainage.

Applications

- ✓ Roofing applications including cedar shingles and shakes
- ✓ Metal roofing applications
- ✓ Zinc roofing applications
- ✓ Siding applications
- ✓ Other roofing applications*

** For more information on roofing applications, please contact our office at 877-514-5336*

Features and Benefits

Drainage of excess moisture and ventilation in one product

Lightweight and easy to handle

Simple installation with mechanical staple hammer

Polymer core resistant to most known corrosive chemicals, including solvents

Wide rolls for fewer seams

Core absorbs and releases no moisture

Provides no source for the promotion of MOLD, MILDEW or BACTERIA



0.30" (7.6 MM) CORE

Physical Properties

Description	Means of Measurement English/Metric		Value English/Metric	
Flame Spread	ASTM E84		Class A	
Core Polymer	Nylon, UV-Stabilized			
Thickness	Inches	Mm	0.30	7.6
Total Weight	oz/yd ²	g/m ²	9.9	335.7

Packaging

Description	Means of Measurement English/Metric		Value English/Metric	
Core Width	Inches	CM	48.0	122
Length	Feet	Meters	60.0	18.3
Area	Square Feet	Square Meters	240	22.3
Roll Diameter	Inches	CM	16.0	40.6
Roll Weight	Pounds	Kg	16.5	7.5

See installation instructions for methods and procedures.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



P.O. Box 241353

Mayfield Heights, OH 44124

Info@KeeneBuilding.com

www.KeeneBuilding.com

877 | 514 | 5336

P 440 | 605 | 1020

F 440 | 605 | 1120