

Product Data

Driwall™ Mortar Deflection 0.5-040

A Masonry Drainage Device

The Keystone™ Cut

Description

Driwall™ Masonry Mortar Deflection 0.50-040 is a 0.375-inch (9-mm), three-dimensional geometric patterned core.

Masonry mortar deflection products are designed to catch and hold mortar droppings. The product allows moisture to pass through, but collects debris above the flashing and below the face of the interior wall in order to allow moisture to flow through to the weep holes.

Driwall™ Mortar Deflection 0.50-040 is placed in a strip horizontally in a 1.0-inch (2.5-cm)-or-less cavity wall. The product is made from polypropylene and designed to be 10.0-inches (25.4-cm) high within the structure.

Driwall™ Mortar Deflection HELPS PREVENT MOLD and does not absorb moisture.

Applications

- ✓ Commercial and residential masonry cavity walls that are 1.0 inch thick OR LESS
- ✓ Commercial and residential masonry cavity walls that are greater than 1.0 inch with additional insulation
- ✓ Stone cavity walls

Features and Benefits

Cavity drainage and protection of flashing in one product


Simple installation with mechanical staple hammer

WILL NOT GROW MOLD; prevents fungus and mildew

Unlike nylon (polyamide), it absorbs NO MOISTURE

Polymer core is resistant to most known corrosive chemicals, including solvents

Perfect width to suspend mortar droppings above weep holes, but below the flashing connection to the interior wall



Physical Properties

Description	Means of Measurement		Value	
	English	Metric	English	Metric
Core Polymer	Polypropylene, UV-Stabilized			
Thickness	Inches	Mm	0.375	9.0
Core Weight	oz/yd ²	g/m ²	12.6	427
Width	Inches	CM	10.0	25.4
Length	Feet	Meters	50.0	15.2

Packaging

Description	Means of Measurement		Value	
	English	Metric	English	Metric
Roll Diameter	Inches	CM	20.0	51.0
Roll Weight	Pounds	Kg	4.0	1.8
Rolls Per Pallet (4 Rolls Per Bag)			36 (9 Bags)	
Linear Feet (Meters) Per Pallet			1800 (554)	
Pallets Per Truck			28	
Linear Feet (Meters) Per Truck			50,400 (15,508)	

See installation instructions for methods and procedures.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



P.O. Box 241353
 Mayfield Heights, OH 44124
 Info@KeeneBuilding.com
 www.KeeneBuilding.com

877 | 514 | 5336
 P 440 | 605 | 1020
 F 440 | 605 | 1120