

## Product Data

# Driwall™ Membrane Adhesive

A Solvent-based Adhesive

### Description

Driwall™ Membrane Adhesive is a fast-drying solvent release adhesive. Designed to require a minimum amount of mixing before applications.

Formulated to have outstanding performance with all Keene Driwall Membrane products, Driwall Membrane Adhesive will also work with most asphalt based waterproofing membranes.

### Packaging

- ✓ 5 Gallon Pail

### Properties & Coverage Rate

Description	Measurement
VOC	2.1 lbs/gallon or 250 grams/liter
Viscosity	1250 cps
Density	7.75 lbs/gallon
% Solids	33%
Coverage	Approximately 450 sq ft/gallon when applied at 1 mil

### Application

Suitable for any Driwall Membrane Application

Ensure all surfaces are dry and free of any oil or grease. All surfaces must be clean and free of dust, dirt and any foreign material. If applying over metal, ensure all rust and scale is removed. Thoroughly mix product BEFORE application. For best results use when substrate temperature is above 40°F. Product is formulated for seasonal use. Note: low temperatures and/or high humidity may extend drying time. Apply using a medium nap roller or a soft bristled brush.

Allow adhesive to dry a minimum of 10 minutes at 75°F (23% humidity) before you apply the Driwall Membrane. If adhesive has dried for 2 hours, recoat before applying the waterproof membrane. Cleans up easily with mineral spirits, paint thinner or kerosene.

General Guidelines

KEEP FROM FREEZING

KEEP AWAY FROM OPEN FLAME AND ANY IGNITION SOURCE

MIX PRIOR TO APPLICATION

Close container after each use

Use appropriate protective clothing and eye protection

Avoid prolonged exposure to skin, use in adequately ventilated area. Prolonged exposure may lead to dizziness or headache. NIOSH/MESA respirator.

\*Do not use with coal tar based products

\*May not be compatible with some one-ply roofing systems – check with manufacture

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.