

Product Data

Driwall[™] Membrane 40 mil

Self-Adhesive Air and Vapor Barrier

Description

Driwall[™] Membrane 40 mil thick (1.0 mm) is a self-adhering flashing and waterproofing membrane.

It provides an air and vapor barrier for full wall, or flashing applications in masonry, wood, or gypsum construction. This highly adhesive, 40 mil membrane insures air and vapor protection.

Storage:

Protect from weather. Store in enclosed area, which is not subject to high heat $(120^{\circ}F)$. Store rolls on end, and on original pallets.

Not intended for permanent exposure to the elements. Cover as soon as possible.

Applications

- Provides an air and vapor barrier for full wall, or flashing applications
- Masonry, wood, or gypsum construction

Features and Benefits

Impermeable to air, moisture vapor, and water Excellent self adhesion to plywood, oriented strand board (OSB), concrete, metal, and like materials Flexible at low temperatures (-20°F) Handles easily at low temperatures (-20°F) Highly resistant to punctures and tears

40 mil (1.0 MM) CORE

Properties

Description	Measurement	
Flame Spread	Self-Extinguishing	
Color	Black	
Thickness	40 mil 1.0 mm	
Elongation (ASTM D412)	200% minimum	
Tensile Strength (ASTM D412)	5000 psi minimum	
Puncture Resistance (ASTM E154)	200 lb	
Moisture Absorption (ASTM D570)	0.2%	
Air Leakage at 75 Pa (ASTM E2178)	0.0001 CFM/ft ²	
Service Temperature	-40° F to 158° F	

Packaging

Description	Measurement	Measurement	
Length	75.0 ft	22.8 m	
Roll Width	12.0 in.	304.8 mm	
	18.0 in.	457.2 mm	
	36.0 in.	914.4 mm	

See installation instructions for methods and procedures.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



 Info@KeeneBuilding.com
 P 440 | 605 | 1020

 KeeneBuilding.com
 F 440 | 605 | 1120

877 | 514 | 5336 P 440 | 605 | 1020 20.1 F 440 | 605 | 1120 page 2/2