

Product Data

Driwall™ Membrane 60 mil

Self-Adhesive Waterproofing Membrane

Description

Driwall™ Membrane 60 mil thick (1.5 mm) self-adhering flashing and waterproofing membrane.

It provides an self-adhered waterproofing membrane in above and below grade applications such as concrete foundation walls, plaza decks, balconies, tunnels and breezeways.

Storage:

Protect from weather. Store in enclosed area, which is not subject to high heat (120°F). Store rolls on end, and on original pallets.

Not intended for permanent exposure to the elements. Cover as soon as possible. Do not use in contact with PVC or vinyl products.

Applications

- ✓ Concrete foundation walls
- ✓ Plaza decks
- ✓ Tunnels
- ✓ Parking decks
- ✓ Foundation waterproofing
- ✓ Balconies

Features and Benefits

Impermeable to air, moisture vapor, and water

Excellent self adhesion to plywood, oriented strand board (OSB), concrete, metal, and like materials

Flexible at low temperatures (-20°F)

Handles easily at low temperatures (-20°F)

Highly resistant to punctures and tears

60 mil (1.5 MM) CORE

Properties

Description	Measurement	
Flame Spread	Self-Extinguishing	
Color	White	
Thickness	60 mil	1.5 mm
Tensile Strength Membrane (ASTM D412)	390 psi	
Tensile Strength Film (ASTM D882)	6,242 psi	
Puncture Resistance (ASTM E154)	331.8 lbs (1475.9N)	
Water Vapor Permeation (ASTM E96)	0.0152 perms	
Moisture Absorption (ASTM D570-81)	0.2%	
Low Temperature Flexibility (ASTM D1970)	Unaffected at -45°F	
Hydrostatic Head (ASTM D5385)	197 ft	

Packaging

Description	Measurement	
Roll Width	12 in.	36 in.
Roll Size	12 in. x 67 ft.	36 in. x 67 ft.
Coverage per Carton	200 sq. ft.	200 sq. ft.
Rolls per Carton	2	1

See installation instructions for methods and procedures.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.